

**ARTICLE 13.00
ADDITIONAL YARD REGULATIONS**

- SECTIONS: 13.01 Number of Main Buildings on Tract
13.02 [Reserved]
13.03 Adjustments to Front Yard Requirements
13.04 Adjustments to Side Yard Requirements
13.05 Projections From Buildings
13.06 Porches and Terraces in Front Yards
13.07 Projection of Terraces, Porches, Platforms, and Ornamental Features
13.08 Double Frontage Lots
13.09 Intersection Safety Zone

13.01 NUMBER OF MAIN BUILDINGS ON TRACT. No more than one main building shall be located on a tract or lot when used for residential purposes. Where a lot or tract is used for an agricultural, commercial, or industrial purpose, more than one main building may be located upon the lot or tract, but only when such buildings conform to all open space requirements around the lot or tract for the district in which the lot or tract is located.

13.02 [Reserved.] (*amended by MC16-55-01*)

13.03 ADJUSTMENT TO FRONT YARD REQUIREMENTS. Where, on the effective date of this ordinance, forty percent (40%) or more of a frontage was occupied by two or more buildings, then the front yard is established in the following manner:

- (A). Where the building further most from the street provides a front yard not more than ten (10) feet deeper than the building closest to the street, then the front yard for the frontage is and remains an average of the then existing front yards.
- (B). Where this (A) is not the case and a lot is within one hundred (100) feet of a building on each side, then the front yard is a line drawn from the closest front corners of these two adjacent buildings.
- (C). Where neither (A) nor (B) is the case, and the lot is within one hundred (100) feet of an existing building on one side only, then the front yard is the same as that of the existing adjacent building.

13.04 ADJUSTMENT TO SIDE YARD REQUIREMENTS. Buildings with side yard setbacks less than required by this ordinance, may have additions erected in line with the existing building and provided further that said addition will be erected no closer to the lot line than the existing building.

13.05 PROJECTIONS FROM BUILDINGS. Every part of any required yard shall be open to the sky and unobstructed except:

- (A). Eaves may project into a front or rear yard thirty-six (36) inches, exclusive of gutters;

ADDITIONAL YARD REGULATIONS

- (B). Eaves may project into a side yard twenty-four (24) inches, exclusive of gutters;
- (C). Ordinary projection of sills, belt courses, cornices, vertical solar screen, and ornamental features which may project twelve (12) inches;
- (D). Air conditioners, not to exceed five (5) ton unit or parts thereof, any project into a required side yard, provided that such projections shall be distant at least three (3) feet from the adjacent lot line and shall not extend more than three (3) feet from the building. Such air conditioners may project into a required front yard, but shall not extend more than three (3) feet from the building, and such air conditioner may extend into one side of a corner lot;
- (E). Solar collectors which are a part of the main building may extend into a required rear yard for a distance not to exceed ten (10) feet.

13.06 PORCHES AND TERRACES IN FRONT YARDS. An open, unenclosed porch may project into a required front yard for distance not exceeding ten (10) feet. Balconies and paved terraces may project into a required front yard for a distance not exceeding six (6) feet. An enclosed vestibule containing not more than forty (40) square feet may project into a required front yard for a distance not to exceed four (4) feet.

13.07 PROJECTION OF TERRACES, PORCHES, PLATFORMS, AND ORNAMENTAL FEATURES. Terraces, uncovered porches, platforms, and ornamental features which do not extend more than three (3) feet above the floor level of the ground (first) story may project into a required side or rear yard, provided these projections be distanced at least three (3) feet from the adjacent side lot line.

13.08 DOUBLE FRONTAGE LOTS. Where lots have double frontage, the required front yard shall be provided on both streets.

13.09 INTERSECTION SAFETY ZONE *(amended by MC16-94-07 07-17-07)*

- (A). There shall be no obstructions, such as buildings structures, grain bins, baled agricultural products, farm machinery, vehicles or other objects, not including vegetation, within fifty (50) feet from a State, County, or section line highway right-of-way or thirty (30) feet from a platted right-of-way.
- (B). Intersection Safety Zone Requirements
 - 1) At every intersection of two roads or a road and a railroad right-of-way, there shall be a intersection safety zone triangle. Within the triangle, no obstructions such as structures, parking or vegetation shall be allowed between two and one half (2.5) feet and ten (10) feet above the elevation of the roadway. Agricultural crops, such as corn, are exempt from this regulation. Fences shall conform to Section 12.01 of this ordinance.
 - 2) Such intersection safety zone triangles shall be formed by the intersection centerlines and a line connecting points on the centerlines of the intersection roads or railroad right-of-way one hundred (100) feet distant from the intersecting centerlines.